

Life Is On



by Schneider Electric



# Get ahead of time!

EVlink™ Wallbox — easy, fast, and robust,  
as charging stations should be.



phone: 021 764 205, email: [contact@evchargingsolutions.nz](mailto:contact@evchargingsolutions.nz)

# Charge and go



## Up to 10 times faster\*

Depending on your electric vehicle and your EVlink Wallbox charging power, you can charge up to 10 times faster than a domestic socket outlet.

## Simply plug in and charge!

When the light on the front of your wallbox starts blinking, you know your charge has started.

## Optimum user protection

Powered by a dedicated branch circuit in your electrical switchboard that has been checked by a qualified electrician, EVlink Wallbox can operate with enhanced reliability and without disrupting the rest of your electrical system.

Unlike domestic socket outlets, EVlink Wallbox is designed to deliver a high charging current for long periods of use on a daily basis.

EVlink Wallbox complies with full electric and plug-in hybrid vehicle charging standards.



## Lean on the expertise of a qualified electrician.

The EVlink Wallbox is installed by a qualified electrician who makes sure that your electrical system complies with standards.



## Save money, stay comfortable.

Decide to charge only during off-peak hours to reduce your electricity bill or adjust charging power when too many appliances are running at the same time in your home.



# Robust outdoor wallbox for homes and private properties (condominium, corporate car park, hotel, etc.)

EVlink Wallbox performs like any familiar home appliance so that you can “fill up” your car with total ease and peace of mind.



Attached cable version



Socket outlet version

## Built to last

- Designed to endure everyday use
- Improved resistance to sunlight

## Peace of mind

- Use restricted by key
- Nobody but you can stop the charging
- No possibility to withdraw the charging cable if locked

## Easy to use

- User-friendly design and intuitive interface
- Light indicator of charging status
- One-touch stop/restart

## Technical information

**Dimensions:** H480 mm x W330 mm x D170 mm

**Wall-mounted installation:** allow at least 80 cm free space to the right of the charging station

**Weight:** 5.6 Kg (with socket outlet), 7.5 Kg (with attached cable)

**Attached cable length:** 4 m

**Operating temperature:** -30 °C to +50 °C

**Weather and shock resistance suitable for an outdoor use:** IP54, IK10

## Average time to fully charge a 24 kWh car battery



Connection to the vehicle	Single phase		Three phase	
	3.7 kW	7.4 kW	11 kW	22 kW
T2 socket outlet	EVH2S3P02K	EVH2S7P02K	EVH2S11P02K	EVH2S22P02K
T2 socket outlet with protective shutters	EVH2S3P04K	EVH2S7P04K	EVH2S11P04K	EVH2S22P04K
Attached cable with T1 connector	EVH2S3P0AK	EVH2S7P0AK		
Attached cable with T2 connector	EVH2S3P0CK	EVH2S7P0CK	EVH2S11P0CK	EVH2S22P0CK

Available information on  
environmental impact mitigation



Life Is On



by **Schneider** Electric

Get the most out of  
your electric  
vehicle.